

SLP-D220

2인치 직접 감열식
데스크탑 라벨 프린터



유통



병원·약국



우편·택배



창고관리

Slim and Specialized



스탠다드



Serial Parallel USB

옵션



Serial Ethernet USB

듀얼 인터페이스

- 스탠다드형: USB + Serial + Parallel
- 옵션형: USB + Serial + Ethernet

탁월한 제품 설계

- 최고 6 ips (152 mm/sec)의 인쇄속도
- 데이터 처리가 빠른 메모리 탑재
- 2인치 이하 용지 전용 슬림한 디자인
- 에너지 고효율 제품



BIXOLON®
a Better Solution for your Business™

SLP-D220

2인치 직접 감열식 데스크탑 라벨 프린터



Standard



Peeler

우수한 호환성

주요 프로그래밍 언어와 호환성이 높습니다.



BPL-Z™

BPL-Z™

사용자 중심의 디자인


- 다양한 타입의 센서가 탑재되어 있습니다.
- 용지 가이드를 조절해 손쉽게 용지 교체가 가능합니다.



Transmissive sensor
(Gap, Media sensor)



Reflective sensor
(Black Mark Sensor)



Min. width 15mm

빅솔론 Label Artist™

엑셀, 텍스트, 액세스 파일 등으로 작성된 데이터베이스를 불러와 출력하거나 사용자가 직접 라벨 디자인을 변경할 수 있는 프로그램을 무상으로 제공하고 있습니다.

제품사양

Printer Specifications

Print Method	Direct Thermal
Print Speed	SLP-D220: Up to 6 ips (152 mm/sec) SLP-D223: Up to 4 ips (100 mm/sec)
Print Resolution	SLP-D220: 203 dpi SLP-D223: 300 dpi
Print Width	SLP-D220: Up to 54 mm SLP-D223: Up to 56.9 mm
Print Length	6 ~ 2000 mm
Sensor	Transmissive, Reflective (adjustable), Head open

Media Characteristics

Media Type	Gap, Black Mark, Notch, Continuous, Fan-Fold
Media Width	15 ~ 60 mm
Media Roll Diameter	Up to 130 mm
Media Thickness	0.06 ~ 0.20 mm
Supply Method	Easy Paper Loading

Physical Characteristics

Dimensions (WxLxD)	120 x 230 x 170 mm (4.72 x 9.05 x 6.69 inch)
Weight	1.36 kg (2.99 lbs.)
Power	EnergyStar Certified, External Power Adaptor 100-240V AC, 50/60Hz

Performance Characteristics

Memory	8MB SDRAM, 4MB FlashROM
Interface	Dual Interface Standard: USB + Serial Optional: Serial+Ethernet

Environment Characteristics

Temperature	Operating: 0 ~ 40°C (32 ~ 104°F) Storage: -20 ~ 60°C (-4 ~ 140°F)
Humidity	Operating: 10 ~ 80% RH Storage: 10 ~ 90% RH

Software

Emulation	SLCS, BPL-Z™, BPL-E™
Driver / Utility	Windows Driver, Linux CUPS Driver, Mac Driver, Utility Program, Label Artist™
SDK	Android SDK, Windows SDK

Fonts / Graphics / Symbolologies

Fonts	• 10 SLCS Resident Bitmap Fonts • One SLCS Resident Scalable Font • 23 Code Page
Graphics	Supporting user-defined fonts, graphics, formats, and logos
Barcode Symbolologies	1D: Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, IMB, Interleaved 2-of-5, ITF, UCC/EAN-128, UPC-A, UPC-E 2D: Data Matrix, MaxiCode, PDF417, QR code

Options

Ethernet, Peeler, Auto Cutter

BR-SLP-D220-KR-SEP15-V1

Copyright © BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

BIXOLON®

www.bixolon.com



BIXOLON Co., Ltd.

경기도 성남시 분당구 판교역로 241번길
20 (삼평동 685) 7~8층 (우13494)

Tel 031 218 5500

Fax 031 218 5589

E-mail sales@bixolon.com

BIXOLON America Inc.

3171 Fujita St Torrance,
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

BIXOLON Europe GmbH

Tiefenbroicher Weg 35, 40472
Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de